

ISIS II RECOIL DAMPER ORDER FORM

Please print and complete this form, enclose your cheque and post to the address above.

NAME:

DELIVERY ADDRESS:

TELEPHONE NO (day) POSTCODE:

..... (or evening):

EMAIL ADDRESS:

CHEQUE ENCLOSED FOR: £
(please make cheques payable to Recoil Systems)

We now accept Credit & Debit Cards
Telephone us on +44 (0) 1763 837 140
if you prefer to pay by credit/debit card.

WHICH ISIS II RECOIL SYSTEM WOULD YOU LIKE TO ORDER?

ISIS II LIGHT - STANDARD MODEL
PLEASE TICK WHICH SHOCK ABSORBER YOU WOULD LIKE FITTED TO YOUR ISIS II RECOIL DAMPER:

SOFT or MEDIUM (SEE NOTES BELOW)

ISIS II LIGHT - TRAP MODEL
THE ISIS II TRAP MODEL IS FOR PRE-MOUNTED DISCIPLINES. IT IS DESIGNED FOR 24grm - 32grm LOADS AND IS AVAILABLE FOR O/U AND S/S GUNS ONLY

ISIS II LIGHT - SEMI-AUTO MODEL (SHORT)
FOR SHORTENED SEMI-AUTO STOCKS, 84mm OVERALL (INCLUDING 11mm GREEN PAD, FOR 24 - 28grm LOADS ONLY (32grm LOADS BY SPECIAL ORDER).

£199 inc. VAT

SPECIAL OFFER

BUY THE RECOIL DAMPER & GREEN PAD FOR ONLY £220 inc. VAT!
(£237 if bought separately.)

BUY THE RECOIL DAMPER & FULLY ADJUSTABLE 20mm PAD FOR ONLY £260 inc. VAT!
(£282 if bought separately.)

Price includes shipping within mainland UK. Shipping is available outside the UK, please contact us for a quotation at: david@recoilsystems.com or tel/fax: +44 (0)1763 837140

CHOICE OF SHOCK ABSORBER:

To give optimum recoil absorption there are two interchangeable shock absorbers available for the ISIS II Recoil Damper Standard Model (not Trap Model). The shock absorbers are classified as SOFT and MEDIUM

- a) if 24grm - 32grm loads are to be used, we would recommend the SOFT unit
- b) if 32grm - 36grm loads are to be used, we would recommend the MEDIUM unit
- c) If the unit it to be fitted to a semi-auto, we would recommend the SOFT unit for 24grm - 36grm loads.

PLEASE NOTE:

The damper unit allows the gun to move backwards into the shoulder by about 6mm (1/4") when the gun is fired. If your gun has a high comb, it may need to be reduced slightly to avoid contact with your cheek during recoil.

If the Standard Model is to be fitted to a semi-auto, a minimum dimension of 100mm (4") is needed between the face of the pad/butt plate and the stock bolt. This allows for a 10mm/12mm butt plate to be used.